

New Tri-Axle 13.6m Curtainsider

Chassis Details

External Length: External Width: Kingpin: Neck Depth: Axle Centers: 13700mm 2550mm 1700mm 158mm 1310mm Fifth Wheel:1250mmGross Trailer Weight:39000 kgsKingpin Weight:15000 kgsBogie Design Weight:24000 kgs

Body Details

Overall Height: Internal Length: Internal Width: Main Rail Centers: Wheel Base:

4200mm 13450mm 2540mm 1200mm 8100mm

Side Aperture Height: 2677mm Rear Aperture Width: 2400mm

Axles & Suspension:

3 off SAF axles with 22.5" Intra disc brakes and 9 tonne air suspension. Knorr Bremse EBS (2S/2M) braking system, including load sensing and roll stability. Spring brake chambers & auto slack adjusters. 2 line braking system with C type couplings. Auto reset raise lower valve is fitted N/S rear. Park & shunt valve fitted N/S at landing legs.

Chassis:

IPEA80 crossmembers @ 350mm pitch closing to 300mm from behind bogie.
125x65 PFC side rave.
8mm rubbing plate with single king pin position.
2 pairs of ferry rings are fitted.
Rope hooks NOT fitted
29mm Wisatrans floor fitted, with recessed 3 piece dump plate at rear (1150mm inside trailer).
Raised coupling box fitted.

Landing Legs:

Fontaine / Fuwa heavy duty landing legs (2 speed) with rocking feet. Landing leg handle fitted UK nearside.

Electrics:

24V electrical system with 2 x 7-pin (24N + 24S) connectors. Aspock wiring loom complete with double LED hamburger tail-lights, LED fog light, LED reverse light, & LED marker lights. 2 off rear upper marker lights fitted (not 6). Aspock square type number plate holder fitted. Additional reversing lights shown on photo not fitted.

Wheels:

6 off Continental 385/65 R22.5 tyres fitted to 11.75 x 22.5 steel rims (120mm offset). Thermoplastic mudwings with antispray flaps (Concept Logo).

Sideguards:

Anodised alloy sideguard rails fitted to galvanised steel hinged uprights.

Rear Underrun:

100mm RHS crashbar with separate lighting panel. Rear step fitted O/S rear.

Buffers:

1 pair of twin roller buffers fitted at rear of chassis.

Front Bulkhead:

Pressed steel corner posts (powder coated). Flush fitted GRP panel is fitted. 160mm high steel kickstrip.

Rear Bulkhead:

Powder coated rear frame with pressed channel pillars. Full height ply/metal rear doors with double galvanised steel locking gear and door hinges. Wire rope door retainers fitted.

Roof:

Alloy cant rails c/w one piece alloy roof sheet.

Load Securing:

Two strap rails fitted to center of roof c/w 13pair of straps.

Sliding Posts:

2no fitted on each side (staggered).

Curtains:

PVC 2x2 weave curtains c/w fixed straps and Euro buckles @ 625mm centers. Curtains are tensioned front with ratchet tensioners and rear with lever tensioners. Pelmet colour is Black.

Paint:

Chassis and body are fully shotblasted before being powder coated through our 2 stage primer/ gloss process.

Colours:

Chassis, landing legs & hubs– TBC. Body posts, front GRP panel & barn doors – Orange, code TBC Curtains – Orange, code TBC

Miscellaneous:

- (1) Signwriting not included.
- (2) Conspicuity tape fitted to curtains (white) & rear doors (red).